

Wall cable duct



Facade profile M (3m) 25x35x25

- Easy to install.
- Universal applicable.
- Impact-resistant.
- Ability to drill holes over the entire length of the cable duct.
- Suitable to cover up existing COAX-cable ducts.
- Paintable with use of primer.
- Easy to saw.
- Increased UV resistance.

Article no:	AT29124
EAN:	8712259604428
Amount Packaging	8 lgt. x 3 m
Degree of protection (IP)	IP40
Material	Plastic
Height	25 mm
Width	35 mm
Length	3000 mm
Halogen free	No
Useful cross section	875 mm ²
Type of fastening	Other
Colour	Grey
RAL-number	7042
Material quality	Polyvinyl chloride (PVC)
Surface protection	Untreated
Transparent	No
Anti-bacterial treatment	No
Impact strength	IK07
Operating temperature	-20 - 60 °C
Cover model	None
Suitable for circuit integrity	No
Number of permanent partitions	
Number of plug-in partitions	
With cable fixing clip	No
With protective foil	No
With duct connector	No
Delivery on roll	No
Pre-stamping	No
Dispatch	8

The wall cable duct is used on Multi Dwelling Units. It can be used to cover up new-toinstall fiberglass cables, but also to cover up existing smaller sized cable ducts which have been used over the years for example to cover up COAX-cables. Because of the higher demand in broadband these units are in need for fiberglass, which can be installed by using the existing smaller sized cable ducts. The wall cable duct will provide a neat visual finish by covering up both the fiberglass cables as well as the cable ducts installed in the past.