

Central junction boxes hollow ceiling



Ceiling junction box cover, square with terminal block

- Quick assembly thanks to plug-in contacts with spring clamp.
- The plug-in clamp is provided with a protective cover.
- Flat design, so that the welding space in the central box is used optimally.
- Suspension hook and 2 screws M4x14 fixed in the lid.
- M4 bolts fitted with a combi head; suitable for automatic screwdriver.
- Universally applicable to any square central box.

Article no:	AT4015
EAN:	8712259004129
Halogen free	Yes
Amount Packaging	100 st.
plugin terminal	Yes
RAL-number (similar)	1013
Material	Plastic
Width	69 mm
Length	69 mm
Diameter	
Type of fastening	Screw cover
Colour	White
Model	Cover with hook
Depth	
Shape	Square
Sealable	No
With screws	Yes
For box-/housing length	72 mm
For box-/housing width	72 mm
With cable outlet	No
Dispatch	100

The junction boxes for hollow ceilings can be used in any situation in the hollow ceiling structure. In rachel wood ceilings (eg. 18 mm and 22 mm) and metal Metal Stud ceilings (eg. 27 mm). Suitable for ceiling panel thicknesses of eg 9.5 mm, 12.5 mm and 25 mm. Applicable in standard and fire-resistant ceiling structures. The round shape of the junction boxes is easily applied in the ceiling plate when drilling the correct hole diameter (Ø 76 mm). The ceiling junction boxes are equipped with 12 combi-inlets. Suitable for 16 mm or 19 mm conduits and cable (via cable strain relief, Art. No. AT1062). The junction boxes can be performed pluggable with WINSTA RD connectors.