


Z25/F25 Cable ducts

F25 Trunking base + cover, 2 m cream (RAL 1013)

- Supplied with special cover for applications in which regulations require that the conduit cannot be opened by hand.
- Includes slots and nail holes.
- Internal dimensions: 22.5 x 10.5 mm



| | |
|--------------------------------|--------------------------|
| Article no: | AT5601 |
| EAN: | 8712259272801 |
| Colour | - |
| Amount Packaging | 5 lgt. x 2 m |
| Degree of protection (IP) | - |
| Material | Plastic |
| Height | 13 mm |
| Width | 25 mm |
| Length | 2000 mm |
| Halogen free | No |
| Useful cross section | 154 mm ² |
| Type of fastening | - |
| RAL-number | 1013 |
| Material quality | Polyvinyl chloride (PVC) |
| Surface protection | Untreated |
| Transparent | No |
| Anti-bacterial treatment | No |
| Impact strength | - |
| Cover model | Loose |
| Suitable for circuit integrity | Yes |
| Number of permanent partitions | |
| Number of plug-in partitions | |
| With cable fixing clip | Yes |
| With protective foil | No |
| With duct connector | Yes |
| Delivery on roll | No |
| Pre-stamping | No |

Z25 and F25 are the most popular surface-mount systems for installation-friendly data cabling. The clever accessories make it possible to use the entire volume of the ducts for data cables up to Ø 10 mm. Every accessory ensures a minimum bending radius of 25 mm. The clickers and guide pieces make installation quick and easy. The special cover makes the F25 ideal for public areas, such as in Fibre to the Home projects in high-rise buildings and stairways. Since the cover is difficult to remove, it cannot be opened by unauthorised persons and, therefore, the chance of interference in telephone, Internet and television signals is reduced.