

Installation 2.0 Cables

Eca - aansluitsnoer dimmer, Male - open eind, 3 meter

- Suitable for use in hollow spaces
- Maintenance-free according to EN-IEC 61535
- Equipped with Attema connectors



Article no:	AT8325.03
EAN:	8712259548463
Amount Packaging	10 st.
Fire class	Eca
Line function	Dimmer (3x1,5)
Cable type	H05VV-F
Length (M)	3 m
Number of poles	4
Rated voltage	400 V
Rated current	16 A
Degree of protection (IP)	IP20
Pollution degree	2
Halogen free	No
Colour outer sheath	Black
Reaction-to-fire according to EN 13501-6: Class	Eca
Reaction-to-fire according to EN 13501-6: Smoke production	None
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	None
Reaction-to-fire according to EN 13501-6: Acidity	None
Housing material	Polyamide (PA)
Total length	3000 mm
Rated surge voltage	4 kV
Cable diameter	8.9 - 8.9 mm
Housing colour	Black
Mechanical coding	Yes
Pole codification	Other
Colour coding/contact insert	Blue
RAL-number coding/contact insert	8002
Type of locking	Integrated in plug-in connector
Fire load	1.02 kWh
Contact material	CuZn
Surface treatment contacts	Tinned
Continuity resistance	
Type of finished cable	Other
Type side 1	Plug
Type side 2	Free conductor end
Conductor end treatment	Ultrasonic compressed wire ends
Dismantle length	90 mm
Strip length	12 mm
Nominal cross section conductor	1.5 mm ²

Insulating piece permanent temperature-resistant	90 °C
Cable permanent temperature-resistant to	60 °C
Max. operating temperature at conductor	50 °C
Dispatch	10

Installation 2.0 is a pluggable installation system based on pre-wired central and cable boxes in combination with prefabricated mounted switching material and a pluggable group box. These components are connected with flexible cables. The installation time is therefore greatly reduced compared to traditional installation, and failure costs are kept to a minimum.