

DATASHEET

FTU DeltaFiber NL

Article number: AT12372



Product description

The DeltaFiber NL FTU is a compact fiber termination unit. It can be applied as a final fiber termination point at residential or business fiber installations. The FTU is the connection between the fiber network and the Network Termination Unit (NTU). The NTU can be connected with the DeltaFiber NL FTU by using a single mode simplex SC patchcord. The FTU is suitable for fiber optic cables with max. 2 fibers. It provides mechanical protection and fiber management and easy to install. There is also a possibility to seal off the connections in order to prevent unauthorized opening.

Features and Benefits

- Easy to install
- Orderly assembly sequence
- Universal applicable (for indoor use)
- Multiple sealable (lid and 2 connector-holders)
- Suitable for most connectors SC / APC
- Suitable for splice protectors ANT, mini heatshrink and heatshrink Ø2,4x45mm
- Integrated cable retention

Technical characteristics

Manufacturer:	Attema
Material:	Molded Plastic, halogen-free
Dimensions :	H=150mm W=80mm D=38mm
Weight:	0,2 kg
Colour:	FTU: White
	Connector-holders: Grey
Dropcable diameters:	max. Ø 8 mm
Number of cable ports in:	1
Number of adapters SC / APC:	2
Splice tray capacity:	2 splice protectors ANT/mini heatshrink or heatshrink Ø2,4x45mm
Fiber bending radius:	R = 23mm
Looping length of fibers:	25 cm

END OF DATASHEET