

DATASHEET

Hybrid Fiber Management Box, AT29336 Ø5,5-10 mm – 192ANT / 4mm + Window Cut

Hybrid Fiber Management Box, AT29337 Ø5,5-10 mm – 96ANT / 8mm + Window Cut

Hybrid Fiber Management Box, AT29338 Ø5,5-10 mm – 96HS / 8mm + Window Cut

Product Description



Hybrid FMB 16v + Window Cut

The hybrid Fiber Management Box (FMB) is suitable for feeder cable (Window Cut) and up to 16 direct buried FttX subscriber drop cables or ducts. The window cut makes it possible to create a Cascade system. The FMB includes a metal wall mounting plate.

The Fiber Management back plate provides an easy entry watertight seal and integrated retention for each individual cable or duct from Ø5,5-10 mm. After the splicing the FM-Box is mounted watertight on a wall or in a street cabinet with the wall mounting plate. Being able to directly insert 10mm ducts makes it an ideal solution for the “Förderprojekte” in Germany.

Maximum splice capacity 192 splice protectors sandwich ANT or mini heatshrink or 96 heatshrink splice protectors.

Features FM Box

- Hybrid entry ports Ø5,5-10 mm
- Integrated cable or duct retention
- Easy entry seal for each individual cable or duct
- Structured management of cables, ducts and fusion splices
- Suitable for direct buried cables or ducts
- Suitable for multiple gas blocks
- Protection class IP65
- Window Cut
- Ready to start kit
- Easy to install
- Compact in size
- Impact resistant
- Halogen-free
- Saving labour costs
- No special tools required

Product codes

AT29336, Hybrid FiberManagement Box – 192ANT / 4mm splice tray + Window Cut
 AT29337, Hybrid FiberManagement Box – 96ANT / 8mm splice tray + Window Cut
 AT29338, Hybrid FiberManagement Box – 96HS / 8mm splice tray + Window Cut

FiberManagement Box for drop cable / duct Ø 5,5-10 ± 0,1 mm + Window Cut.
 Including: 8 splice trays (16 for art.nr. AT29336), 4 stainless steel bolts, 20 cable dummies (black), 1 moisture absorbent lid with laser warning, a metal wall mounting plate, plate mounting kit with nylon plugs Ø6mm, stainless steel screws and a Window Cut kit. Delivered in cardboard box.

Packaging en labelling

All products suitably packed in recyclable materials and clearly labelled with Attema article number and description.

Physical characteristics

Dimensions FM Box:	39 x 22 x 15 cm
Weight FM Box:	3 kg
Wall mounting plate:	Stainless steel plate
Colour:	Grey
Number of cable / duct ports:	1 Window Cut (2 ports) + 16 drop cables/ducts
Number of splice trays:	8 splice trays (16 for art.nr. AT29336)
Splice tray capacity 12HS / 8mm:	12 splice protectors heatshrink Ø2,4 x 45mm
Splice tray capacity 12ANT / 8mm:	12 splice protectors ANT or mini heatshrink
Splice tray capacity 12ANT / 4mm:	12 splice protectors ANT or mini heatshrink (1,3 x 30mm)
Fiber bending radius:	R = 30mm
Looping length of fibres:	30 cm
Feeder cable:	Ø 4,5 mm up to including Ø 8,3 mm
Customer cable / duct	Drop cable / duct: Ø 5,5 – 10,0 ± 0,1 mm.

Technical characteristics

Cable/duct retention in FM back plate:	>100 - 223N (depending on the Ø cable – duct)
Cable torsion:	90 degrees, 400mm No degradation, no leakage.
Impact protection:	IK10, EN 62262 No degradation, no leakage.
Ingress protection:	IP65, EN 60529 No leakage
Skullpressure:	1000N per 25cm ² (force applied without acceleration for a duration of 10 minutes) No degradation, no leakage.
Vibration:	10 Hz, Amplitude 3mm, during 10 days, No failure
Temperature:	Storage – 10 °C / + 60 °C Installation – 10 °C / + 60 °C In use – 35 °C / + 60 °C

Permanent UV radiation may influence the properties of this product.

END OF DATASHEET

www.attema.com