

DATASHEET

Hybrid FttX Street Cabinet (16v), AT29326 Ø5,5-10 mm – 192ANT / 4mm + Window Cut
 Hybrid FttX Street Cabinet (16v), AT29327 Ø5,5-10 mm – 96ANT / 8mm + Window Cut
 Hybrid FttX Street Cabinet (16v), AT29328 Ø5,5-10 mm – 96HS / 8mm + Window Cut

Product Description



FttX Street Cabinet



Hybrid FM-Box (16v) + Window Cut

The hybrid Fiber Management Box (FMB) is suitable for feeder cable (Window Cut) and up to 16 direct buried FttX subscriber drop cables or ducts. The window cut makes it possible to create a Cascade system. The FMB includes a metal wall mounting plate. Together with the stainless steel street cabinet Attema creates a fast, easy to install and reliable above the ground distribution point.

The Fiber Management back plate provides an easy entry watertight seal and integrated retention for each individual cable or duct from Ø5,5-10 mm . After the splicing the FM-Box is mounted watertight in the street cabinet with the wall mounting plate. Being able to directly insert 10mm ducts makes it an ideal solution for the “Förderprojekte” in Germany.

Maximum splice capacity 192 splice protectors sandwich ANT or mini heatshrink or 96 heatshrink splice protectors.

Features hybrid FM Box

- Hybrid entry ports Ø5,5-10 mm
- Integrated cable or duct retention
- Easy entry seal for each individual cable or duct
- Structured management of cables, ducts and fusion splices
- Suitable for direct buried cables or ducts
- Suitable for multiple gas blocks
- Protection class IP65
- Window Cut
- Ready to start kit
- Easy to install
- Compact in size
- Impact resistant
- Saving labour costs
- No special tools required

Features FttX Street Cabinet

- 60-80µm Polyester Powder coating
- Integrated Foundation
- Stainless Steel
- Universal ½ Euro cylinder
- Weather resistant mounting panel
- Detachable front panel
- Premounted fixation points for ducts and cables

Product codes

AT29326, Hybrid FttX Street Cabinet (16v) – 192ANT / 4mm + Window Cut
 AT29327, Hybrid FttX Street Cabinet (16v) – 96ANT / 8mm + Window Cut
 AT29328, Hybrid FttX Street Cabinet (16v) – 96HS / 8mm + Window Cut

FttX Street cabinet + hybrid FiberManagement Box for drop cable / duct 5,5-10 ± 0,1 mm + WC
 Including: 8 splice trays (16 for art.nr. AT29326), 4 stainless steel bolts, 20 cable dummies (black), 1 moisture absorbent, a lid with laser warning, a metal wall mounting plate, plate mounting kit with nylon plugs Ø6mm, stainless steel screws and a Window Cut kit. Delivered in cardboard box.

Packaging en labelling

All products suitably packed in recyclable materials and clearly labelled with Attema article number and description.

Physical characteristics FttX Street Cabinet

Dimensions Street Cabinet (HxWxD)	1170 x 500 x 250
Dimensions installation panel (HxWxD)	600 x 490 x 18
Material:	Stainless steel
Foundation	Integrated
Color	Grey (RAL7035)
Coating	60-80 µm polyester powder coating

Physical characteristics hybrid FM-Box

Dimensions FM Box:	39 x 22 x 15 cm
Weight FM Box:	3 kg
Wall mounting plate:	Stainless steel plate
Colour:	Grey
Number of cable / duct ports:	1 Window Cut (2 ports) + 16 drop cables/ducts
Number of splice trays:	8 splice trays (16 for art.nr. AT29326)
Splice tray capacity 12HS / 8mm:	12 splice protectors heatshrink Ø2,4 x 45mm
Splice tray capacity 12ANT / 8mm:	12 splice protectors ANT or mini heatshrink
Splice tray capacity 12ANT / 4mm:	12 splice protectors ANT or mini heatshrink (1,3 x 30mm)
Fiber bending radius:	R = 30mm
Looping length of fibres:	30 cm
Feeder cable:	Ø 4,5 mm up to including Ø 8,3 mm
Customer cable / duct	Drop cable / duct: Ø 5,5 – 10,0 ± 0,1 mm.

Technical characteristics

Cable/duct retention in FM back plate:	>100 - 233 (depending on the Ø cable – duct)
Cable torsion:	90 degrees, 400mm No degradation, no leakage.
Impact protection:	IK10, EN 62262 No degradation, no leakage.
Ingress protection:	IP65, EN 60529 No leakage
Skullpressure:	1000N per 25cm ² (force applied without acceleration for a duration of 10 minutes) No degradation, no leakage.
Vibration:	10 Hz, Amplitude 3mm, during 10 days, No failure
Temperature:	Storage – 10 °C / + 60 °C Installation – 10 °C / + 60 °C In use – 35 °C / + 60 °C

Permanent UV radiation may influence the properties of this product.

END OF DATASHEET

www.atterma.com